

# 3M™ DBI-SALA® ExoFit™ XE200 Comfort Wind Energy Positioning Safety Harness with auto-locking quick connect buckles

# Part number(s):

1112744 (Size 1) 1112745 (Size 2) 1112746 (Size 3)

# **Description**

Sub-brand:	DBI-SALA®
Industry:	Wind Energy
Applications:	Climbing, Positioning

#### **Features**

Features			
Rear fall arrest attachment point:	<ul><li>Large stand-up D-ring</li><li>Aluminium - blue anodisation</li></ul>		
Front fall arrest attachment point:	Standard D-ring     Aluminium - blue anodisation		
Work positioning Attachment points:	Large cranked D-ring     Aluminium - blue anodisation		
Leg Buckles:	<ul> <li>Auto-locking quick connect</li> <li>Steel - zinc plated/black paint, aluminium - grey anodisation</li> </ul>		
Chest Buckles:	Quick connect     Steel - zinc plated/black paint,     aluminium - grey anodisation		
Waist Buckles:	<ul> <li>Auto-locking quick connect</li> <li>Steel - zinc plated/black paint, aluminium - grey anodisation</li> </ul>		
Adjustment:	<ul> <li>Legs, waist, torso</li> <li>Torso: Revolving adjuster</li> <li>Steel/aluminium - ratchet buckle</li> </ul>		
	- Steel/aluminium - ratchet buckle		
Webbing:	45mm Polyester		
Webbing: Thread:			
	45mm Polyester		
Thread:	45mm Polyester  Polyester  Front & rear fall indicators  Leg, shoulder & waist padding  2x Auto-resetting/repositionable lanyard keepers  RFID Equipped  Suspension trauma straps  Dedicated personal self-retracting lifeline		




Front



Back

# 3M™ DBI-SALA® Fall Arrest Harness sizing chart



## Weight

	<b>∢</b> ····>	kg
1112744	Size 1	2.90
1112745	Size 2	2.95
1112746	Size 3	3.00



### Important notice

The mounting and use of the product described within this document assumes that the user has previous experience of this type of product and that it will be assembled by a competent professional according to product documentation. Before any use of this product it is recommended to complete some trials to validate the performance of the product within its expected application.

All information and specification details contained within this document are inherent to this specific 3M product and would not be applied to other products or environment. Any action or usage of this product made in violation of this document is at the risk of the user.

Compliance to the information and specification relative to the product contained within this document does not exempt the user from compliance with additional guidelines (safety rules, procedures). Compliance to operational requirements especially in respect to the environment and usage of tools with this product must be observed. The 3M Group (who cannot verify or control these elements) would not be held responsible for the consequences of any violation of these rules which remain external to its decision and control.

Warranty conditions for products are determined with the sales contract documents and with the mandatory and applicable law, excluding any other warranty or compensation.



